











**THERMOPLASTIKI**

DECLARATION OF PERFORMANCE

No. 02.001 – 305/11/EU – 13/April/2020

ALU Sliding

1. Unique identification code of the product type: **S650 PHOS**
2. Intended use: **Homes, Office buildings, Store buildings, Industrial buildings, Malls**
3. Manufacturer: **THERMOPLASTIKI S.A. Amigdaleonas, Kavala
P.C. 64012**
4. Authorised representative: **Not applicable**
5. AVCP System (evaluation and confirmation of performance stability): **3**
6. Harmonised Standard:
Notified laboratory: **EN 14351-1:2006
ift Rosenheim Nr: 0757**
7. Declared performance/s:

TYPE		1	2	3	4	5	6
PRESENTATION							
Standard / Essential Characteristics							
	Wind pressure resistance EN 12210	C3/B3	C3/B3	C3/B3	C3/B3	C3/B3	C3/B3
	Waterproofing EN 12208	9A	9A	9A	9A	9A	9A
	Air permeability EN 12207	4	4	4	4	4	4
	Resistance to transverse shear stress EN 13115	npd	npd	npd	npd	npd	npd

**THERMOPLASTIKI**

	Torsion resistance EN 13115	npd	npd	npd	npd	npd	npd
	Resistance to use EN 12400	npd	npd	npd	npd	npd	npd
	Impact resistance EN 13049	npd	npd	npd	npd	npd	npd
	Thermal permeability EN 10077	1,1-3,8	1,1-3,8	1,1-3,8	1,1-3,8	1,1-3,8	1,1-3,8
	Reaction to fire EN 13501-1	npd	npd	npd	npd	npd	npd
	Hazardous substances	npd	npd	npd	npd	npd	npd

8. Appropriate technical documentation and/or specific technical documentation: **The technical requirements and the performance of the products are documented in products' Technical Documentation and in the Company's Technical Brochures.**

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued in accordance with Regulation (EU) No. 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Despoina Germanidou, Products Certification Manager

Amigdaleonas, Kavala,

13/04/2020